

PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines



ACCU



110/230 V



110/230 V

Model	Nanoflow	Microflow Touch	Microflow LOG
Typical Usage	Inside	Inside	Inside
Fiber/Cable OD	0.8 - 3 mm	0.8 - 6.5 mm	0.8 - 6.5 mm
Duct Size OD	3 - 10 mm	5-16 mm	5-16 mm
Part no. #	101-160601800	101-10051	101-171001001
Max Speed	150 m/min (490 ft)	90 m/min (295 ft)	90 m/min (295 ft)
Blowing distance	Up to 1200 m (3940 ft)	Up to 2500 m (8200 ft)	Up to 2500 m (8200 ft)
Rec. Airflow	0-500 l/min (0-17.7 cfm)	200-500 l/min (7.1-17.7 cfm)	200-500 l/min (7.1-17.7 cfm)
Rec. Pressure	0-10 bar air (0-150 psi)	8-16 bar air (120-230 psi)	8-16 bar air (120-230 psi)
Length	212 mm	Machine: 250 mm	Machine: 250 mm
Width	104 mm	Control Box: 200 mm	Control Box: 240 mm
Height	139 mm	150 mm	150 mm
Weight	2.8 kg (w/o battery)	220 mm	220 mm
		9.7 kg	11.3 kg
		Control Box: 1.9 kg	Control Box: 1.9 kg
Unique features	<ul style="list-style-type: none"> Fully automatic Unique double fiber protection Battery-powered No tool needed Easy load and removal of pre-connected products Easy-to-read LED display Multiple positions Lightweight but powerful 	<ul style="list-style-type: none"> Auto-Buckle Detection Adjustable Torque Preset Automatic Stop Adjustable Speed Control Speed, Torque & Count Display Air Pressure & Flow Regulation Easy to Operate Simple Maintenance 	<ul style="list-style-type: none"> Software operated Electronic Hardware Modern Connectivity Verification of job quality Auto-buckle Detection Adjustable Torque Preset Automatic Stop Adjustable Apeed Control




PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines



HYDRAULIC



HYDRAULIC



HYDRAULIC

Model	MiniFlow RAPID	PowerFlow	MultiFlow
Typical Usage	Outside	Outside	Outside
Fiber/Cable OD	4-12 mm	8-25 mm	8-32 mm
Duct Size OD	7-20 mm	18-70 mm	18-70 mm
Part no. #	101-10031	101-10001	101-10002
Max Speed	100 m/min (325 ft)	80 m/min (260 ft)	80 m/min (260 ft)
Pushing Force	0-40 kg	0-125 kg	0-200 kg
Blowing distance	Up to 3500 m (11485 ft)	Up to 10000 m* (32810 ft)	Up to 10000 m* (32810 ft)
Rec. Airflow	1000 l/min (35.3 cfm)	8000-12000 l/min (282.5 - 423.8 cfm)	8000-12000 l/min (282.5 - 423.8 cfm)
Rec. Pressure	8-16 bar air (120-230 psi)	8-12 bar air (120-170 psi)	8-12 bar air (120-170 psi)
Length	650 mm	650 mm	700 mm
Width	225 mm	230 mm	230 mm
Height	210 mm	350 mm	350 mm
Weight	24 kg	38 kg	40 kg
Unique features	<ul style="list-style-type: none"> • Use with Air or Water* • Push Force Monitor • Rugged Construction • Flexible Adaptability • Adjustable Torque Distance and Speed measurement • Ease of Use • Simple Maintenance 	<ul style="list-style-type: none"> • Use with Air or Water* • Only for Single Cable • Rugged Construction • Flexible Adaptability • Adjustable Torque Distance and Speed measurement • Ease of Use • Simple Maintenance 	<ul style="list-style-type: none"> • Use with Air or Water* • Relining or Single Cable • Rugged Construction • Flexible Adaptability • Adjustable Torque Distance and Speed measurement • Ease of Use • Simple Maintenance

